2 2 0 C

2 1 5 C / R

Array: 90 x 7 1 line / 2.1" / 15 char.

215 C/R 220 C 320 C 🚥 330 C 420 C/R --- OR-BIG DOT

• 2-, 3- or 4-inch Characters

• Red or tri-color • Networkable via RS232, RS485 or

Ethernet adapter (optional) • Programmable via remote keyboard or

• Viewing distance up to 200 feet

ALPHA software

Case: 57.4" x 5.5" x 3.8"

11AM - 5PM Case: 37.7" x 3.8" x 2.9"

3 2 0 C

3 3 0 C

Array: 120 x 7 1 line / 3.1" / 20 char.

Array: 120 x 7

1 line / 2.1" / 20 char.

Today's SAFET Case: 84.4" x 5.5" x 3.8"

Array: 180 x 7 1 line / 3.1" / 30 char.



Ideal for use in retail, factories, warehouses and service industries.

Two-Line

PPD G/R OR OR

4080 C

4120 C/R --- OR -

4160 C/R --- OR -

4240 C/R --- OR -

• .7- to 4.8-inch Characters

• Standard and NEMA enclosures available

• Viewing distance up to 240 feet

• Networkable via RS232, RS485 or Ethernet adapter (optional)

• Ideal for use in manufacturing, warehouses, call centers and lobbies

• Programmable via remote keyboard or ALPHA software

Ideal for use in manufacturing, warehouses,

call centers, lobbies and schools.

• Red, green or tri-color

door Models



Case: 71.9" x 7.8" x 5.6"

4 2 0 R / C Array: 120 x 7

1 line / 4" / 20 char.

DOT

Case: 49" x 6.25" x 4.25"

Array: 80 x 7 1 line / 4" / 13 char.

BIG

(Not to scale) Case: 13.7" x 3.5" x 1.84"

PPD G/R Array: 120 x 7

Product

Case: 40.2" x 7.7" x 5.1"

4 0 8 0 C Array: 80 x 16 1 line / 4.8" / 8 char.

2 lines / 2.1" / 13 char.

2 lines / .7" / 20 char.

Case: 28.2" x 7.7" x 5.5" TOM MTG. 9AM Thursday

4 1 2 0 C / R

Array: 120 x 16 1 line / 4.8" / 12 char. 2 lines / 2.1" / 20 char.

Array: 160 x 16

Assembly today Case: 52.2" x 7.7" x 5.1"

Case: 64.2" x 7.7" x 5.1"

1 line / 4.8" / 16 char. 2 lines / 2.1" / 26 char.

4 1 6 0 C / R

4 2 0 0 C / R Array: 200 x 16 1 line / 4.8" / 20 char. 2 lines / 2.1" / 33 char.

or all of customer and employee

Case: 76.2" x 7.7" x 5.1"

4 2 4 0 C / R

Array: 240 x 16


1 line / 4.8" / 24 char.

2 lines / 2.1" / 40 char.

→ 7 0 8 0 C Array: 80 x 24 1 line / 7.2" / 8 char. 2 lines / 3" / 13 char. 3 lines / 2.1" / 13 char.

4 lines / 1.5" / 16 char.

Threet door Models



- 1.5- to 7-inch Characters
- Tri-color
- Standard and NEMA enclosures available • Networkable via RS232, RS485 or Ethernet adapter (optional)
- Programmable via remote keyboard or ALPHA software • Viewing distance up to 350 feet



call centers and lobbies.

Fourt Line

9080 C ••• OR •

9120 C

9240 C

• Networkable RS232, RS485 and built-in Ethernet interface

Ideal for use in factories, warehouses,

call centers and lobbies.

• Ideal for use in retail, factories, warehouses and service industries

• 1.5- to 9.6-inch Characters

• Enhanced sound capability • Programmable via ALPHA software

• Viewing distance up to 480 feet

• Standard enclosure

• Tri-color

oor Models



Case: 40.2" x 10" x 5.4"

7 1 2 0 C

Array: 120 x 24 1 line / 7.2" / 12 char. 2 lines / 3" / 20 char. 3 lines / 2.1" / 20 char. 4 lines / 1.5" / 24 char.



PERCENTAGE

Array: 160 x 24

7 2 0 0 C

9080C

9 1 2 0 C

9 1 6 0 C

9 2 0 0 C

9 2 4 0 C

1 line / 7.2" / 16 char. 2 lines / 3" / 26 char. 3 lines / 2.1" / 26 char. 4 lines / 1.5" / 32 char.

Array: 200 x 24

1 line / 7.2" / 20 char. 2 lines / 3" / 33 char. 3 lines / 2.1" / 33 char. 4 lines / 1.5" / 40 char.

Array: 80 x 32 1 line / 9.6" / 9 char.

2 lines / 4.5" / 9 char. 3 lines / 3" / 9 char. 4 lines / 2.1" / 13 char. 5 lines / 1.5" / 16 char.

Array: 120 x 32 1 line / 9.6" / 13 char. 2 lines / 4.5" / 13 char. 3 lines / 3" / 13 char. 4 lines / 2.1" / 20 char. 5 lines / 1.5" / 24 char.

Array: 160 x 32 1 line / 9.6" / 17 char.

2 lines / 4.5" / 17 char. 3 lines / 3" / 17 char.

4 lines / 2.1" / 26 char. 5 lines / 1.5" / 32 char.

5 lines / 1.5" / 40 char.

Array: 200 x 32 1 line / 9.6" / 22 char. 2 lines / 4.5" / 22 char. 3 lines / 3" / 22 char. 4 lines / 2.1" / 33 char.







Case: 28" x 12" x 2.2"






it our web site today



Case: 64" x 12" x 2.2"



www.sunhealthsys.com Case: 76" x 12" x 2.2"

Array: 240 x 32 1 line / 9.6" / 26 char. 2 lines / 4.5" / 26 char. 3 lines / 3" / 26 char. 4 lines / 2.1" / 40 char. 5 lines / 1.5" / 48 char.



• 1.4- or 2.1-inch Characters • Tri-color, superbright red and red

Text-only messages • Viewing distance up to 100 feet

- **Full Matrix**
- or employee communications

• Minimum 2.1" Characters • Tri-color • Text and graphic display • Viewing distance starting at 100 feet • Standard and NEMA enclosures • Networkable via RS232, RS485 or Ethernet adapter (optional) • Programmable via ALPHA software • Ideal for manufacturing and warehouse data management, theaters

Oak / 1.4" / 8 x 16 Aluminum / 1.4" / 8 x 16 Aluminum / 1.4" / 8 x 24

DIRECTOR


Encased in beautiful solid oak or aluminum, the Director is designed for high-visibility indoor use in offices, lobbies, conference rooms, boardrooms,

showrooms, or any area that requires a sophisticated message center. Displays data in 3 vivid colors,

perfect for these applications: • Bank or hotel lobby - point of purchase info • Event and conference room scheduling • Activities/events board - front office greetings • Personnel in/out - employee announcements

- Wireless IR remote control • PC control with AlphaNET





Synchronized clocks • Multiple time zone support



For more information, check all that apply:

☐ Smart Alec[®] ☐ AlphaNET ALPHA Messaging Software ☐ AlphaNET Market Ticker

Messaging Software

- ☐ ActiveX
- **ALPHA Outdoor**
- ☐ ALPHAEclipse 1500 Time/Temperature
- ☐ ALPHAEdipse 2500 ☐ ALPHAEclipse 3500
- NAME

ADDRESS

CITY / STATE / ZIP

ORGANIZATION

TITLE PHONE

EMAIL

Call Centers ☐ Commercial/Retail

☐ Financial Industrial Automation

☐ Sports

Other

Transit ☐ Theaters

Please fill out the attached card and mail to

or call toll free:

or visit our web site @

idaptivedisplays.com



MILWAUKEE WI 53224-9976 7840 NORTH 86TH STREET ADAPTIVE MICRO SYSTEMS INC

POSTAGE WILL BE PAID BY ADDRESSEE

FIRST-CLASS MAIL PERMIT NO. 11093 MILWAUKEE, WI

IF MAILED NECESSARY **NO POSTAGE** BUSINESS REPLY MAIL



ALPHAECLIPSE 1500 TIME AND TEMPERATURE

- All-weather LED Time and Temperature
- 18-inch segmented-character design
- Red or amber
- Two choices for digit style: a rounded contemporary look, or a traditional squared-off segment format
- Single-faced, double-faced and other configurations available
- Viewing distance up to 900 feet

ALPHAECLIPSE 2500 SERIES

- 2-, 4-, 6-, 8- and 10-line Models
- 7- to 36-inch characters
- Red or amber
- Networkable via RS232, RS485 or wireless interface (optional)

2500	Columns	Char. Per Line	3500	Columns	Char. Per Line
2	96 to 192	16 to 32	1	64 to 144	10 to 24
4	96 to 192	16 to 32	2	64 to 144	10 to 24
6	96 to 192	16 to 32	3	64 to 128	10 to 21
8	96 to 192	16 to 32	4	64 to 128	10 to 21
10	96 to 192	16 to 32			

ALPHAECLIPSE 3500 SERIES

- 1-, 2-, 3- and 4-line Models
- 11- to 44-inch Characters
- Red or amber
- Networkable via RS232, RS485 or wireless interface (optional) and wired modem configurations Programmable via ALPHA software
- Viewing distance up to 2200 feet
- Ideal for outdoor use in schools, banks, auto dealers, stadiums and many other commercial business applications

TA® Software



AlphaNET MESSAGING SOFTWARE

Create, edit, revise and schedule messages and graphics to single or multiple ALPHA displays. Used in employee communications and the retail and service-related industries.

- Supports text, graphics and counter international characters
- Message scheduling options • Task Bar creation tools
- Calendar date scheduling of messages

Interface sign connection: PC Serial COM port Serial to IR loader Ethernet network Modem

- Includes Jasc® Paint Shop Pro[™]
- Animation library and GIF file support Diagnostic utility included
- Includes trial version of AlphaNET Market Ticker*

Smart Aleco Intelligent Messaging software

PC-based tools to acquire, manage and distribute critical real-time information, such as production, material handling, or call center status.

- Prioritizes and schedules message delivery
- Acquire data from other applications via DDE, sockets and OPC • Monitor information systems for changes in activities or events
- Multi-user support • Conditions indicators with colors, strobes or audible alarm
- PC serial COM ports or Ethernet network • Supports all ALPHA displays, TAP-compatible pagers and MAPI-compliant email
- PC Serial Connection: Ethernet to print/serial server

Local area paging (TAP) to receiver or pager Wide area wireless (RCC) to pager

Manual data entry - Editor Input: Output: Socket interface

DDE OPC **ALPHA** displays Pagers Email

ALPHA Active X ®

ALPHA ActiveX comes complete with everything you need to trigger messages and alarms and to display real-time information. Communicate with ALPHA electronic signs from any application that supports the use of ActiveX controls.

- Display real-time information and statistics
- Display event or alarm conditions • Control text attributes such as color, font, flashing, etc.
- Directly display your existing database messages • Easy to install and use

Connection: PC Serial COM port Ethernet network

• No setup fee. Low monthly service fee. • Display individual stock name, symbol, last price and change

from all the major North American exchanges.

AlphaNET plug-in. Used for selecting and displaying 20-minute delayed stock quotes

- Plug-in for AlphaNET V2.0 or later
- 20-minute delayed market information
- Available in 10- and 50-symbol services

* AlphaNET Market Ticker

- Data received via Internet
- Display DOW, NASDAQ, S&P500, AMEX and TSE indices • Compatible with all ALPHA Indoor and Outdoor displays

ALPHA MESSAGING SOFTWARE

Application to create and program messages to a single ALPHA LED display from a desktop PC. Used in applications such as employee communications, retail or service industries.

- Easy creation of text messages
- Flexible and efficient programming • Specific text attributes
- Easy to use and install

Connection: PC COM Port

*Check our website for all the latest offerings!

Contact your ALPHA Distributor today!

Get the message. Get ALPHA... The first name in quality electronic communication.

Call 1-800-558-7022 for the ALPHA Distributor nearest you! Or stop by our web site @ www.adaptivedisplays.com

© Copyright 2001 Adaptive Micro Systems, Inc. All rights reserved. AlphaNET and AlphaVision are trademarks and ALPHA, Big Dot and Smart Alec are registered trademarks of Adaptive Micro Systems, Inc. Other product names appearing are the property of their respective owners. Windows, Windows 95, and Windows NT, as well as Word, are registered trademarks of Microsoft Corporation. No affiliation is expressed or implied herewith, and no warranty as to the use and operation of such products belonging to third parties is being made herewith.

Printed in the USA.



www.adaptivedisplays.com



200 Series

300 Series

9000 Series

7000 Series

Window Display **Director Series**

AlphaVision

Big Dot **Eclipse PPD** Time/Temp Serial Clock Get the message.™

Software Solutions